




PHOTO	NOM	TYPE	CARACTÉRISTIQUES
	GP-400 1/4	BASE OMNIDIREC.	380-520 MHz - 150 W - 0dB (2,15 dBi)
	CVX-400	BASE OMNIDIREC.	Ver imagen/See image - 100 W - Ver imagen/See image
	KAD-UHF	BASE OMNIDIREC.	Ver imagen/See image - 150 W - 5,5dB(7,65 dBi)
	BP-UHF	BASE OMNIDIREC.	UHF - 100 W - 1 dBd (3,15 dBi)
	GPC-400 TB	BASE OMNIDIREC.	400-520 MHz - 250 W - 5,5dB (7,65 dBi)
	DA-4309	DIRECTIVA	430-440 MHz - 500 W - 10,85 dB (13dBi)
	AUC-3	DIRECTIVA	600-630 MHz - 300 W - 5dB (7.15dBi)
	DA-4319	DIRECTIVA	430-440 MHz - 1000 W - 14,05 dB (16,2dBi)
	AUC-5	DIRECTIVA	Ver cuadro/ See Picture - 500 W - 9 dBd (11,15dBi)
	MU-70	MOVIL	400-500 MHz - 50 W - 2,15 dBi
			

	UH-7 PRO	MOVIL	380-520 MHz - 150 W - 0dB (2,15dBi)
	UH-50	MOVIL	400-470 MHz - 150 W - 4dBd (6,15 dBi)
	DESIRER UHF	MOVIL	400-500 MHz - 300 W - 3dBd (5,15dBi)
	UH-1400	MOVIL	400-500 MHz - 150 W - 0dBd (2,15dBi)
	MU-PRO	MOVIL	380-520 MHz - 50 W - 0dB (2,15dBi)
	UH-4400	MOVIL	380-520 MHz - 150 W - 0dBd (2,15dBi)
	P-400	WALKIE	380-520 MHz - 10 W - 0 dB
	A-400	WALKIE	400-455 MHz - 10 W - 0dB (2,15dBi)
	A-400 A	WALKIE	455-520 MHz - 10 W - 0dB (2,15dBi)