

Semi-rigid cable



UT-86 (RG-405/U)						GROUP	CODE
						22X	CAB-22X-50
Ω	CENTER COND		DIELECTRIC		SCREEN		JACKET
	MATERIAL	$\emptyset$	MATERIAL	$\emptyset$	MATERIAL	$\emptyset$	MATERIAL $\emptyset$
50 $\pm$ 1.5	CU	0.51	PTFE	1.68	CU	2.2	-- --

GHZ	1	2	4	7	10	20
dB/100m	65	95	140	180	220	310
Watts	160	110	70	50	40	30

UT-141 (RG-402/U)						GROUP	CODE
						36X	CAB-36X-50
Ω	CENTER COND		DIELECTRIC		SCREEN		JACKET
	MATERIAL	$\emptyset$	MATERIAL	$\emptyset$	MATERIAL	$\emptyset$	MATERIAL $\emptyset$
50 $\pm$ 1	CU	0.92	PTFE	2.985	CU	3.58	-- --

GHZ	1	2	4	7	10	20
dB/100m	35	52	80	125	160	200
Watts	600	390	250	180	140	100

UT-250 (RG-401/U)						GROUP	CODE
						63X	CAB-63X-50
Ω	CENTER COND		DIELECTRIC		SCREEN		JACKET
	MATERIAL	$\emptyset$	MATERIAL	$\emptyset$	MATERIAL	$\emptyset$	MATERIAL $\emptyset$
50 $\pm$ 0.5	CU	1.63	PTFE	5.31	CU	6.35	-- --

GHZ	1	2	4	7	10	20
dB/100m	22	32	50	70	85	120
Watts	1100	800	500	360	300	200